

AETES

130VDC PSU 1250W-3750W

*Power Boost of 150% for 5s
Industrial Grade Design
Five Year Warranty*




"...power alliance..."

Specification

ITEMS	MODEL	XPM-1P3-130-1250	XPM-1P3-130-2500	XPM-1P3-130-3750
Output Voltage		130VDC		
Max. Output Current (DC)		10A (1250 Watt)	20A (2500 Watt)	30A (3750 Watt)
Input Voltage Range		100V/.../ 240V AC 50/60 Hz (86V...264V 47..63Hz)		
Input Current (120V/ 240V AC)		12,8A/ 6,4A	25,6A/ 12,8A	38,4A/ 19,2A
Output Power Reserve		150% peak load for 5 seconds at <45°C		
Power Factor		0.9 (Meets EN61000-3-2 Class A)		
Overcurrent Protection		>105-150% Constant current style		
Overvoltage Protection		125% -140%		
Hold Up Time (Typ)		20ms		
Efficiency (120V/ 240V AC)		<85% / <88%		
Load Regulation (max.)		864 mV		
Line Regulation (max.)		576 mV		
Ripple Noise (max.)		900 mV		
Remote On/Off		Optionally		
Status Indicator & Dry Contact		Optionally		
Multiple Output Voltage		Optionally (Vout1= 130V Vout2= +5V/.../ +48V)		
Enclosure Color		Grey (RAL7035)		
Operating Temperature		-20°C to 70°C, derating linearly to 50% load above 50°C		
Storage Temperature		-30°C to +75°C		
Humidity (non condensing)		30- 90% RH operating, 10-90% RH non operating		
Cooling		Internal fan		
Withstand Voltage (One minute)		Input to Ground 2kVAC, Input to Output 3kVAC, Output to Ground 500VAC		
Isolation Resistance		>100MΩ at 25°C & 70%RH, Output to Ground 500VDC		
Vibration Compatibility		MIL-STD-810F 514.5 CAT. 4,10		
Shock Compatibility		<196.1 m/s ²		
Immunity Compatibility		EN61000-4 - 2 -3 -4 -5 -6 -8 -11		
Safety Compatibility		EN60950-1		
EMI Compatibility		EN55011 / EN55022-B, FCC Class B		
Weight (Typ)		9,0 kg	13,3 kg	15,8 kg
Dimensions (mm)		F:140 B:250+20 C:315	F:150 B:320+20 C:315	F:150 B:370+20 C:315
Warranty		5-YEAR		

Drawing



"...power alliance..."



AETES
"...power alliance..."

The specifications, drawings and images indicated in this document are based on current information. All content is subject to modifications or additions. For more information on our local sales offices, visit us at our website below.